







PLAN
Scale A


LEGEND

-  Coloured concrete pathway threshold treatment
-  Potential turf refer project drawings for application
-  General concrete pathway
-  Traffic island treatment either coloured concrete infill treatment OR landscaped garden bed
-  Coloured concrete median infill treatment
- Refer project drawings for colour and surface treatment of concrete areas

NOTES:

1. Ensure median cut though freely drains to road carriageway.
2. Kerb ramps to be installed perpendicular (normal) to direction of travel.
3. Tactile ground surface indicators (TGSIs) to comply with AS1428.4: Tactile Indicators
4. Where site conditions permit traffic signal pedestal to be:
 - ≤1000mm clear of back of kerb.
 - 600mm maximum clear of Kerb Ramp.
 - 600mm maximum clear of "slot" opening
5. Minimum luminance contrast between the colour of the path and the colour of the TGSIs shall be in accordance with AS1428.4.1 and the colour of TGSIs shall not be yellow.
6. All dimensions are in metres unless noted otherwise.

REVISIONS		INIT	DATE	Drawn	BW	Date	07/16
E				Coordinator	PP	Date	07/16
D				AUTHORIZED  07/07/16 Manager Integrated Transport Planning & Design RPEQ 6872			
C							
B							
A							
ORIGINAL ISSUE		BW	07/16				



**PEDESTRIAN FACILITIES AT
TRAFFIC ISLAND CUT THROUGH**



DRG No. **PC-2140**

ORIGINAL SIZE **A3** REVISION