



NOTES

- 1. Gate and end posts to be 65x65x2 galvanized steel section to AS 1163.
- 2. Intermediate posts to be 50x50x2 galvanized steel section to AS 1163.
- 3. Panels to be fixed to posts using standard galvanized clips and galvanized M8 bolts.
- 4. Galvanizing to AS 1214 and AS 4792.
- 5. Panels and posts to be powder coated black or as shown on project drawings.
- 6. Concrete N25 minimum in accordance with AS 1379 and AS 3600.
- 7. Posts are to be vertical. Raked panels are available for slopes up to 1 in 5.
- 8. Nuts to be spot welded to bolts as an anti-theft deterent.
- 9. All dimensions are in millimetres unless shown otherwise.
- 10. 100mm wide reflective tape to be applied to end posts where vehicle traffic conflict.
- 11. This type of fencing is not suitable for use in a coastal environment.

REVISIONS	INIT	DATE	SCALES	Drawn	TC	Date	07/17
				Coordinator	PP	Date	07/17
			A 0m 1,0 2,0 3,0 4,0 1,200 AT A3	AUTHORISED			
			1200 AT AS				
;			ŕ	SYD JERRAM 03/07/17			
Concrete maintenance strip removed	TC	8/17					
ORIGINAL ISSUE	TC	06/17		Manager Integ RPEQ 6872	rated Transport	t Planning	g & Design

PEDESTRIAN FENCE POWDER COATED WELDED MESH PANELS

