



← STREET NAME

G3-8(L)

G3-8(L) exiting the roundabout where medians are provided refer MBRC Std Dwgs for mounting details

STREET NAME

G5-1

130mm HIGH TEXT

G5-1 signs on appropriate corner in accordance MUTCD Part 5



D4-1-2(L)

D4-1-2 typical where entering the roundabout



R1-3

R1-3 on median island and verge at dual lanes



R1-3

Potential low level landscaping, as specified. Planting shall not obstruct visibility for pedestrians and motorists. Refer note 6.

TWO LANE ROUNDABOUT WITH BICYCLE PROVISIONS

Scale A

NOTES:

1. This drawing should be used as a guide for the installation of signs around roundabouts
2. For the geometric design refer to Austroads Guide to Road Design – Part 4B: Roundabouts.
3. Use of D4-1-2A signs may not be required in local streets where the posted speed limit is ≤50km/h. Use where intersection layout is not obvious at a distance equal to the approach sight distance. For speed limits of 60 or 70km/h, use D4-1-2B. for speed limits of 80km/h, use D4-1-1A.
4. Street lighting should be designed and installed in accordance with AS1158 and shall not be located in central island.
5. Landscaping:
 - Groundcover to be 500mm max. height above road pavement.
 - Allowable planting zone within 500mm to 1500mm determined by sight distances. Refer standard drawing SL1020.
7. All dimensions are in metres unless otherwise noted.

REVISIONS		INT	DATE	SCALES		Drawn	RM	Date	07/16
E				A 1:500		Coordinator	PP	Date	07/16
D				AUTHORIZED 07/07/16 Manager Integrated Transport Planning & Design RPEQ 6872					
C									
B									
A									
ORIGINAL ISSUE		RM	07/16						

TWO LANE ROUNDABOUT SIGNAGE DETAILS



DRG No. **SI-6015**

ORIGINAL SIZE **A3** REVISION