9.4.1.2 Community facilities zone

9.4.1.2.1 Purpose - Community facilities zone

- The purpose of this part of the Reconfiguring a lot code is to facilitate and manage the outcomes of development for reconfiguring a lot and its associated Operational Works in the Community facilities zone, to achieve the Overall Outcomes.
- The purpose of this part of the code will be achieved through the overall outcomes as identified in Part 9.4.1 -2. Reconfiguring a lot code and the following additional Community facilities zone specific overall outcomes:
- Reconfiguring a lot maintains lots of sufficient size and dimension to facilitate development of a scale and intensity a. consistent with the applicable precinct.
- Lots created for community facilities purposes are strategically located to best service their catchment, whilst having regard to possible impacts on, and from, surrounding uses and infrastructure.
- Reconfiguring a lot avoids areas subject to constraint, limitation, or environmental values. Where reconfiguring C. a lot cannot avoid these identified areas, it responds by:
 - adopting a 'least risk, least impact' approach when designing, siting and locating development to minimise the potential risk to people, property and the environment;
 - ii. ensuring no further instability, erosion or degradation of the land, water or soil resource;
 - maintaining environmental values, including natural, ecological, biological, aquatic, hydrological and amenity values, and enhancing these values through the provision of environmental offsets, landscaping and facilitating safe wildlife movement through the environment;
 - protecting native species and protecting and enhancing native species habitat; iv
 - protecting and preserving the natural, aesthetic, architectural historic and cultural values of significant trees, places, objects and buildings of heritage and cultural significance;
 - establishing effective separation distances, buffers and mitigation measures associated with major infrastructure to minimise adverse effects on sensitive land uses from noise, dust and other nuisance generating activities;
 - ensuring it promotes and does not undermine the ongoing viability, integrity, operation, maintenance and safety of major infrastructure;
 - Ensuring effective and efficient disaster management response and recovery capabilities.
- The Reconfiguring a lot, Operational works associated with the Reconfiguring a lot, and uses expected to occur as a result of the Reconfiguring a lot:
 - i. responds to the risk presented by overland flow and minimises risk to personal safety;
 - is resilient to overland flow impacts by ensuring the siting and design accounts for the potential risks to property associated with overland flow;
 - iii. does not impact on the conveyance of overland flow up to and including the Overland Flow Defined Flood Event:
 - directly, indirectly and cumulatively avoids an increase in the severity of overland flow and potential for iv. damage on the premises or to a surrounding property.
- Reconfiguring a lot achieves the intent and purpose of the Community facilities zone outcomes as identified in Part 6 or where in the Redcliffe Kippa-Ring local plan area, achieves the intent and purpose of the Redcliffe Kippa-Ring local plan and applicable precinct as identified in Part 7.

9.4.1.2.2 Criteria for assessment

Part C - Criteria for assessable development - Community facilities zone

Table 9.4.1.2.1 Assessable development - Community facilities zone

Performance outcomes	Acceptable outcomes
Lot size and design	

P01

Lots are of sufficient size and design to accommodate land uses consistent in the zone and applicable precinct with regard to areas required for:

- buildings and associated structures; a.
- b. convenient and safe access;
- on-site car parking; C.
- d. on-site manoeuvring to ensure vehicle egress and access in forward gear;
- appropriately sited loading and servicing areas; e.
- f. setbacks, buffers and landscaping where required;
- maintaining the required level of functionality during and immediately after a natural hazard event.

Note - refer to the overall outcomes for the Community facilities zone for a list of consistent uses.

No acceptable outcome provided

Boundary realignment

PO₂

Boundary alignments ensure that infrastructure and services are wholly contained within the lot they serve. No acceptable outcome provided.

PO₃

Boundary realignment does not result in:

- existing land uses on-site becoming non-complying with planning scheme criteria;
- b. lots being unserviced by infrastructure;
- lots not providing for own private servicing. C.

Note - Examples of a. above may include but are not limited to:

- minimum lot size requirements; a.
- setbacks b.
- C. parking and access requirements;
- d. servicing and Infrastructure requirements;
- e. dependant elements of an existing or approved land use being separately titled, including but not limited to:

- Where premises is approved as Multiple dwelling (49) with a communal open space area, the communal open space cannot be separately titled as it is required by the Multiple dwelling
- Where a commercial or industrial land use contains an ancillary office $^{\left(53\right)}$, the office cannot be separately titled as it is considered part of the commercial or industrial use.
- Where a Dwelling house (22) includes a secondary dwelling or associated outbuildings, they cannot be separately titled as they are dependent on the Dwelling house (22) use.

AO4

No acceptable outcome provided

PO4

Boundary realignment results in lots which have appropriate size, dimensions and access to cater for uses consistent with the precinct.

Note - Refer to overall outcomes for the Community Facilities zone - and relevant precinct for uses consistent in this precinct.

Reconfiguring existing development by Community Title

PO₅

Reconfiguring a lot which creates or amends a community title scheme as described in the Body Corporate and Community Management Act 1997 is undertaken in a way that does not result in existing uses on the land becoming unlawful or otherwise operating in a manner that is:

- inconsistent with any approvals on which those a. uses rely; or
- inconsistent with the self-assessable development requirements applying to those uses at the time that they were established.

Note - Examples of land uses becoming unlawful include, but are not limited to the following:

- Land on which a Dual occupancy (21) has been established is reconfigured in a way that results in both dwellings no longer being on the one lot. The reconfiguring has the effect of transforming the development from a Dual occupancy (21) to two separate Dwelling houses (22), at least one of which does not satisfy the self-assessment requirements applying to Dwelling houses (22).

 Land on which a Multiple dwelling (49) has been
- established is reconfigured in a way that precludes lawful access to required communal facilities by either incorporating some of those facilities into private lots or otherwise obstructing the normal access routes to those facilities. Those communal facilities may have been required under self-assessment requirements for the use or conditions of development approval.

Editor's note -To satisfy this performance outcome, the development application may need to be a combined application for reconfiguring a lot and a material change of use or otherwise be supported by details that confirm that the land use still satisfies all relevant land use requirements.

Reconfiguring by Lease

PO6

Reconfiguring a lot which divides land or buildings by lease in a way that allows separate occupation or use of those facilities is undertaken in a way that does not result in existing uses on the land becoming unlawful or otherwise operating in a manner that is:

- inconsistent with any approvals on which those uses rely; or
- b. inconsistent with the self-assessable development requirements applying to those uses at the time that they were established.

Note - An example of a land use becoming unlawful is a Multiple dwelling $^{(49)}$ over which one or more leases have been created in a way that precludes lawful access to some of the required communal facilities. Some of the communal car parking facilities have been incorporated into lease areas while other leases are located in a way that obstructs the normal access routes to other communal facilities. Those communal facilities may have been required under self-assessment requirements for the use or conditions of development approval, but they are no longer freely available to all occupants of the Multiple dwelling (49)

Editor's note - To satisfy this performance outcome, the development application may need to be supported by details that confirm that the land use still satisfies all relevant land use requirements.

Editor's note – Under the Sustainable Planning Act, the following do not constitute reconfiguring a lot and are not subject to this performance outcome:

- a lease for a term, including renewal options, not exceeding 10 years; and
- an agreement for the exclusive use of part of the common property for a community titles scheme under the Body Corporate and Community Management Act 1997.

No acceptable outcome provided.

Volumetric subdivision

PO7

The reconfiguring of the space above or below the surface of the land ensures appropriate area, dimensions and access arrangements to cater for uses consistent with the precinct and does not result in existing land uses on-site becoming non-complying with planning scheme criteria.

Note - An example may include but are not limited to:

where a Dwelling house $^{(22)}$ includes a secondary dwelling or associated outbuildings, they cannot be separately titled as they are dependent on the Dwelling house (22)

Reticulated supply

PO8

Each lot is provided with an appropriate level of service and infrastructure, including water supply, stormwater management, sewage disposal, stormwater drainage, electricity, telecommunications and gas (if available) in a manner that:

- is efficient in delivery of service; a.
- b. is effective in delivery of service;
- is conveniently accessible in the event of C. maintenance or repair;
- minimises whole of life cycle costs for that d. infrastructure:
- minimises risk of potential adverse impacts on e. the natural and built environment;
- f. minimises risk of potential adverse impact on amenity and character values;
- recognises and promotes Councils Total Water Cycle Management policy and the efficient use of water resources.

80A

Lots are provided with:

- a connection to the reticulated water supply infrastructure network;
- a connection to the sewerage infrastructure network; b.
- a connection to the reticulated electricity infrastructure network; and
- a physical connection to the telecommunication network, that where available to the land is part of the high speed broadband network.

Stormwater location and design

PO9

Lots are of a sufficient grade to accommodate effective stormwater drainage to a lawful point of discharge.

AO9

The surface level of a lot is at a minimum grade of 1:100 and slopes towards the street frontage, or other lawful point of discharge

PO10

The development is planned and designed considering the land use constraints of the site and incorporates water sensitive urban design principles.

No acceptable outcome provided.

PO11

Stormwater drainage pipes and structures through or within private land are protected by easements in favour of Council with sufficient area for practical access for maintenance.

Note - To determine sufficient areas for easements refer to Planning scheme policy - Integrated design.	
PO12	No acceptable outcome provided.
Stormwater management facilities are located outside of riparian areas and prevent increased channel bed and bank erosion.	
PO13	No acceptable outcome provided.
Natural streams and riparian vegetation are retained and enhanced through revegetation.	
PO14	No acceptable outcome provided.
Areas constructed as detention basins are adaptable for passive recreation.	10, 10,
PO15	No acceptable outcome provided.
Development maintains the environmental values of waterway ecosystems.	
PO16	No acceptable outcome provided.
Constructed water bodies are not dedicated as public assets.	50
ussets.	
Stormwater management system	
	A017
Stormwater management system	AO17 The roads, drainage pathways, drainage features and waterways safely convey the stormwater flows for the defined flood event without allowing flows to encroach upon private lots.
Stormwater management system PO17 The major drainage system has the capacity to safely	The roads, drainage pathways, drainage features and waterways safely convey the stormwater flows for the defined flood event without allowing flows to encroach upon
PO17 The major drainage system has the capacity to safely convey stormwater flows for the defined flood event.	The roads, drainage pathways, drainage features and waterways safely convey the stormwater flows for the defined flood event without allowing flows to encroach upon private lots. AO18
PO17 The major drainage system has the capacity to safely convey stormwater flows for the defined flood event. PO18 Overland flow paths (for any storm event) from roads and public open space areas do not pass through	The roads, drainage pathways, drainage features and waterways safely convey the stormwater flows for the defined flood event without allowing flows to encroach upon private lots. AO18 Drainage pathways are provided to accommodate overland

- a. 100% reductions in mean annual loads from unmitigated development for total suspended solids, total phosphorus, total nitrogen and gross pollutants >5mm;
- the design objectives in Table A and B in Appendix 2 of the SPP.

Note - To demonstrate compliance with this PO a stormwater quality management plan is to be prepared by a suitable qualified person demonstrating compliance with the Urban Stormwater Planning Guideline 2010 and considering any local area stormwater management planning prepared by Council.

Note - Refer to Overlay map - Stormwater catchments for catchment boundaries.

No acceptable outcome provided.

PO20

Where located outside the Upper Pine, Hays Inlet and Burpengary Creek catchments, development achieves the design objectives in Tables A and B in Appendix 3 of the SPP.

Note - To demonstrate compliance with this PO a stormwater quality management plan is to be prepared by a suitable qualified person demonstrating compliance with the Urban Stormwater Planning Guideline 2010 and considering any local area stormwater management planning prepared by Council.

Note - Refer to Overlay map - Stormwater catchments for catchment boundaries.

PO21

The stormwater management system is designed to:

- protect the environmental values in downstream a. waterways;
- maintain ground water recharge areas; b.
- preserve existing natural wetlands and C. associated vegetation buffers;
- d. avoid disturbing soils or sediments;
- avoid altering the natural hydrologic regime in e. acid sulphate soil and nutrient hazardous areas;
- f. maintain and improve receiving water quality;
- protect natural waterway configuration; g.
- h. protect downstream and adjacent properties;
- i. protect and enhance riparian areas.

PO22

Design and construction of the stormwater management system:

- utilise methods and materials to minimise the whole of lifecycle costs of the stormwater management system; and
- b. are coordinated with civil and other landscaping works.

Note - To determine the standards for stormwater management system construction refer to Planning scheme policy - Integrated design.

No acceptable outcome provided.

Native vegetation where not located in the Environmental areas overlay

PO23

Reconfiguring a lot facilitates the retention of native vegetation by:

- incorporating native vegetation and habitat trees a. into the overall subdivision design, development layout, on-street amenity and landscaping where practicable;
- ensuring habitat trees are located outside a b. development footprint. Where habitat trees are to be cleared, replacement fauna nesting boxes are provided at the rate of 1 nest box for every hollow removed. Where hollows have not yet formed in trees > 80cm in diameter at 1.3m height, 3 nest boxes are required for every habitat tree removed.
- providing safe, unimpeded, convenient and ongoing wildlife movement;
- avoiding creating fragmented and isolated d. patches of native vegetation.
- ensuring that biodiversity quality and integrity of habitats is not adversely impacted upon but are maintained and protected:
- f. ensuring that soil erosion and land degradation does not occur;
- ensuring that quality of surface water is not g. adversely impacted upon by providing effective vegetated buffers to water bodies.

No acceptable outcome provided

Noise

PO24

Noise attenuation structure (e.g. walls, barriers or fences):

contribute to safe and usable public spaces, through maintaining high levels of surveillance

AO24

Noise attenuation structures (e.g. walls, barriers or fences):

are not visible from an adjoining road or public area unless;

- of parks, streets and roads that serve active transport purposes (e.g. existing or future pedestrian paths or cycle lanes etc);
- maintain the amenity of the streetscape. b.

Note - A noise impact assessment may be required to demonstrate compliance with this PO. Noise impact assessments are to be prepared in accordance with Planning scheme policy - Noise.

Note - Refer to Planning Scheme Policy - Integrated design for details and examples of noise attenuation structures.

- i. adjoining a motorway or rail line; or
- ii. adjoining part of an arterial road that does not serve an existing or future active transport purpose (e.g. pedestrian paths or cycle lanes) or where attenuation through building location and materials is not possible.
- do not remove existing or prevent future active b. transport routes or connections to the street network;
- C. are located, constructed and landscaped in accordance with Planning scheme policy - Integrated design.

Note - Refer to Planning Scheme Policy - Integrated design for details and examples of noise attenuation structures.

Note - Refe80r to Overlay map - Active transport for future active transport routes.

Values and constraints criteria

Note - The relevant values and constraints criteria do not apply where the development is consistent with a current Development permit for Reconfiguring a lot or Material change of use or Operational work, where that approval has considered and addressed (e.g. through a development footprint plan (or similar in the case of Landslide hazard) or conditions of approval) the identified value or constraint under this planning scheme.

Bushfire hazard (refer Overlay map - Bushfire hazard to determine if the following assessment criteria apply)

Note - The preparation of a bushfire management plan in accordance with Planning scheme policy - Bushfire prone areas can assist in demonstrating compliance with the following performance criteria. The identification of a development footprint will assist in demonstrating compliance with the following performance criteria.

PO25

Lots are designed to:

- minimise the risk from bushfire hazard to each lot and provide the safest possible siting for buildings and structures;
- limit the possible spread paths of bushfire within the reconfiguring;
- achieve sufficient separation distance between C. development and hazardous vegetation to minimise the risk to future buildings and structures during bushfire events;
- d. maintain the required level of functionality for emergency services and uses during and immediately after a natural hazard event.

AO25

Reconfiguring a lot ensures that all new lots are of an appropriate size, shape and layout to allow for the siting of future buildings being located:

- within an appropriate development footprint; a.
- within the lowest hazard locations on a lot;
- to achieve minimum separation between development or development footprint and any source of bushfire hazard of 20m or the distance required to achieve a Bushfire Attack Level BAL (as identified under AS3959-2009), whichever is the greater;
- to achieve a minimum separation between development or development footprint and any retained vegetation strips or small areas of vegetation of 10m or the distance required to achieve a Bushfire Attack Level BAL (as identified under AS3959-2009), whichever is the greater;
- away from ridgelines and hilltops;

	f. on land with a slope of less than 15%;
	g. away from north to west facing slopes.
PO26	AO26
Lots provide adequate water supply and infrastructure	For water supply purposes, reconfiguring a lot ensures that:
to support fire-fighting.	a. Lots have access to a reticulated water supply provided by a distributer retailer for the area; or
	b. where no reticulated water supply is available, on-site fire fighting water storage containing not less than 10 000 litres and located within a development footprint.
PO27	A027
Lots are designed to achieve:	Reconfiguring a lot ensures a new lot is provided with:
a. safe site access by avoiding potential	a. direct road access and egress to public roads;
entrapment situations;	
b. accessibility and manoeuvring for fire-fighting during bushfire.	b. an alternative access where the private driveway is longer than 100m to reach a public road;
during businite.	c. driveway access to a public road that has a gradient no greater than 12.5%;
	d. minimum width of 3.5m.
PO28	AO28
The road layout and design supports:	Reconfiguring a lot provides a road layout which:
a. safe and efficient emergency services access to all lots; and manoeuvring within the subdivision;	includes a perimeter road that separating the new lots from hazardous vegetation on adjacent lots incorporating by:
b. availability and maintenance of access routes	i. a cleared width of 20m;
for the purpose of safe evacuation.	ii. road gradients not exceeding 12.5%;
20	iii. pavement and surface treatment capable of being used by emergency vehicles;
	iv. Turning areas for fire fighting appliances in accordance with Qld Fire and Emergency Services' Fire Hydrant and Vehicle Access Guidelines.
	b. Or if the above is not practicable, a fire maintenance trail separates the lots from hazardous vegetation on adjacent lots incorporating:
	i. a minimum cleared width of 6m and minimum formed width of 4m;
	ii. gradient not exceeding 12.5%;

- iii. cross slope not exceeding 10%;
- a formed width and erosion control devices to the standards specified in Planning scheme policy - Integrated design;
- a turning circle or turnaround area at the end of the trail to allow fire fighting vehicles to manoeuvre;
- passing bays and turning/reversing bays every 200m;
- an access easement that is granted in favour of the Council and the Queensland Fire and Rescue Service or located on public land.
- excludes cul-de-sacs, except where a perimeter road with a cleared width of 20m isolates the lots from hazardous vegetation on adjacent lots; and
- excludes dead-end roads.

Environmental areas (refer Overlay map - Environmental areas to determine if the following assessment criteria apply)

Note - The identification of a development footprint will assist in demonstrating compliance with the following performance criteria.

Editors' Note - The accuracy of overlay mapping can be challenged through the development application process (code assessable development) or by way of a planning scheme amendment. See Council's website for details.

PO29

No new boundaries are to occur within 4m of a High Value Area.

No acceptable outcome provided

PO30

Lots are designed to:

- minimise the extent of encroachment into the MLES waterway buffer or a MLES wetland
- ensure quality and integrity of biodiversity and b. ecological values is not adversely impacted upon but are maintained and protected;
- incorporate native vegetation and habitat trees into the overall subdivision design, development layout, on-street amenity and landscaping where practicable;
- d. provide safe, unimpeded, convenient and ongoing wildlife movement;
- avoid creating fragmented and isolated patches e. of native vegetation;

AO30

Reconfiguring a lot ensures that no additional lots are created within a Value Offset Area.

- f. ensuring that soil erosion and land degradation does not occur;
- ensuring that quality of surface water is not g. adversely impacted upon by providing effective vegetated buffers to water bodies.

AND

Where development results in the unavoidable loss of native vegetation within a MLES waterway buffer or a MLES wetland buffer, an environmental offset is required in accordance with the environmental offset requirements identified in Planning scheme policy -Environmental areas.

Extractive resources transport route buffer (refer Overlay map - Extractive resources to determine if the following assessment criteria apply)

Note - The identification of a development footprint will assist in demonstrating compliance with the following performance criteria.

PO31	No acceptable outcome provided.
Lots provide a development footprint outside of the buffer.	
PO32	No acceptable outcome provided.
Access to a new lot is not from an identified extractive industry transportation route, but to an alternative public road.	SC,

Extractive resources separation area (refer Overlay map - Extractive resources to determine if the following assessment criteria apply)

Note - The identification of a development footprint will assist in demonstrating compliance with the following performance criteria.

PO33	No acceptable outcome provided.
Lots provide a development footprint outside of the	
separation area.	

Heritage and landscape character (refer Overlay map - Heritage and landscape character to determine if the following assessment criteria apply)

Note - The identification of a development footprint will assist in demonstrating compliance with the following performance criteria.

PO34	No acceptable outcome provided
Lots do not:	
reduce public access to a heritage place, building, item or object;	

b. create the potential to adversely affect views to and from the heritage place, building, item or object;		
c. obscure or destroy any pattern of historic subdivision, historical context, landscape setting or the scale and consistency of the urban fabric relating to the local heritage place.		
PO35	No acceptable outcome provided.	
Reconfiguring a lot retains significant trees and incorporates them into the subdivision design, development layout and provision of infrastructure.		
Infrastructure buffers (refer to Overlay map - Infrastructure buffers to determine if the following assessment criteria apply)		
Note - The identification of a development footprint will assist in d	emonstrating compliance with the following performance standards.	
Bulk water supply infrastructure		
PO36	No acceptable outcome provided.	
Reconfiguration of lots does not compromise or adversely impact upon the efficiency and integrity of Bulk water supply infrastructure.	ccue.	
PO37	AO37	
Reconfiguring of lots ensures that access requirements of Bulk water supply infrastructure are maintained.	Bulk water supply infrastructure traversing or within private land are protected by easement in favour of the service provider for access and maintenance.	
PO38	AO38	
Development within a Bulk water supply infrastructure buffer:	New lots provide a development footprint outside the Bulk water supply infrastructure buffer.	
 a. is located, designed and constructed to protect the integrity of the water supply pipeline; b. maintains adequate access for any required maintenance or upgrading work to the water supply pipeline. 		
PO39	No acceptable outcome provided.	
Boundary realignments:		
do not result in the creation of additional building development opportunities within the buffer;		
ii. results in the reduction of building development opportunities within the buffer.		
Gas pipeline buffer		

PO40	No acceptable outcome provided.
New lots provide a development footprint outside of the buffer.	
PO41	No acceptable outcome provided.
The creation of new lots does not compromise or adversely impact upon the efficiency and integrity of supply.	
PO42	No acceptable outcome provided.
The creation of new lots does not compromise or adversely impact upon access to the supply line for any required maintenance or upgrading work.	S' sion
PO43	No acceptable outcome provided.
Boundary realignments:	
i. do not result in the creation of additional building development opportunities within the buffer;	
ii. results in the reduction of building development opportunities within the buffer.	Cho.
High voltage electricity line buffer	60.
PO44	No acceptable outcome provided.
Lots provide a development footprint outside of the buffer.	
PO45	AO45
Adequate buffers are provided between utilities and dwellings to protect residential amenity and health.	New lots provide a development footprint for utilities and dwellings outside of the buffer
PO46	AO46
The creation of new lots does not compromise or adversely impact upon the efficiency and integrity of supply.	No new lots are created within the buffer area.
PO47	AO47
The creation of new lots does not compromise or adversely impact upon access to the supply line for any required maintenance or upgrading work.	No new lots are created within the buffer area.
PO48	No acceptable outcome provided.
Boundary realignments:	

i.	do not result in the creation of additional building development within the buffer;	
ii.	result in the reduction of building development opportunities within the buffer.	
Lan	ndfill buffer	
PO4	49	No acceptable outcome provided.
	v lots provide a development footprint outside of buffer.	·(O)
PO	50	No acceptable outcome provided.
Βοι	ındary realignments:	
i.	do not result in the creation of additional building development opportunities within the buffer;	(8)
ii.	results in the reduction of building development opportunities within the buffer.	
Was	stewater treatment site buffer	
PO	51	No acceptable outcome provided.
	v lots provide a development footprint outside of buffer.	SCI
PO	52	No acceptable outcome provided.
Βοι	ındary realignments:	
i.	do not result in the creation of additional building development opportunities within the buffer;	
ii.	results in the reduction of building development opportunities within the buffer.	
1	delide herend (refer Overlan men. I an delide h	and to determine the following consequent with the
Landslide hazard (refer Overlay map - Landslide hazard to determine if the following assessment criteria apply)		
Note -The preparation of a site-specific geotechnical assessment report in accordance with Planning scheme policy – Landslide hazard can assist in demonstrating compliance with the following performance criteria. The identification of a development footprint on will assist in demonstrating compliance with the following performance criteria.		
PO	53	AO53.1
	s ensure that:	Lots provides a development footprint for all lots free from
a.	future building location is located in part of a site	risk of landslide.
	not subject to landslide risk;	AO53.2
		ı

- the need for excessive on-site works, change to finished landform, or excessive vegetation clearance to provide for future development is avoided:
- there is minimal disturbance to natural drainage patterns:
- d. earthworks do not:
 - involve cut and filling having a height greater than 1.5m;
 - involve any retaining wall having a height ii. greater than 1.5m;
 - iii. involve earthworks exceeding 50m³,
 - iv. redirect or alter the existing flows of surface or groundwater:
- development can be located and designed to e. maintain the required level of functionality during and immediately after a natural hazard event.

Development footprints and driveways for lots does not exceed 15% slope.



Note - The applicable river and creek flood planning levels associated with defined flood event (DFE) within the inundation area can be obtained by requesting a flood check property report from Council.

PO54

Development:

- minimises the risk to persons from overland flow; a.
- does not increase the potential for damage from overland flow either on the premises or on a surrounding property, public land, road or infrastructure.

No acceptable outcome provided.

PO55

Development;

- maintains the conveyance of overland flow predominantly unimpeded through the premises for any event up to and including the 1% AEP for the fully developed upstream catchment;
- does not concentrate, intensify or divert overland flow onto an upstream, downstream or surrounding property.

Note - Reporting to be prepared in accordance with Planning scheme policy - Flood hazard, Coastal hazard and Overland flow...

AO55

Development ensures that any buildings are not located in an Overland flow path area.

Note: A report from a suitably qualified Registered Professional Engineer Queensland is required certifying that the development does not increase the potential for significant adverse impacts on an upstream, downstream or surrounding property.

PO56

Development does not:

- directly, indirectly or cumulatively cause any increase in overland flow velocity or level;
- increase the potential for flood damage from b. overland flow either on the premises or on a surrounding property, public land, road or infrastructure.

Note - Open concrete drains greater than 1m in width are not an acceptable outcome, nor are any other design options that may increase scouring.

Note - A report from a suitably qualified Registered Professional Engineer Queensland is required certifying that the development does not increase the potential for significant adverse impacts on an upstream, downstream or surrounding premises.

Note - Reporting to be prepared in accordance with Planning scheme policy - Flood hazard, Coastal hazard and Overland flow

No acceptable outcome provided.

PO57

Development ensures that overland flow is not conveyed from a road or public open space onto a private lot, unless the development is in a Rural zone.

AO57

Development ensures that overland flow paths and drainage infrastructure is provided to convey overland flow from a road or public open space area away from a private lot, unless the development is in the Rural zone.

PO58

Development ensures that Council and inter-allotment drainage infrastructure, overland flow paths and open drains through private property cater for overland flows for a fully developed upstream catchment flows and are able to be easily maintained.

Note - A report from a suitably qualified Registered Professional Engineer Queensland is required certifying that the development does not increase the potential for significant adverse impacts on an upstream, downstream or surrounding premises.

Note - Reporting to be prepared in accordance with Planning scheme policy - Flood hazard, Coastal hazard and Overland flow

AO58.1

Development ensures that roof and allotment drainage infrastructure is provided in accordance with the following relevant level as identified in QUDM:

- Urban area Level III: a.
- b. Rural area – N/A;
- Industrial area Level V; C.
- d. Commercial area - Level V.

AO58.2

Development ensures that all Council and allotment drainage infrastructure is designed to accommodate any event up to and including the 1% AEP for the fully developed upstream catchment.

PO59

Development protects the conveyance of overland flow such that easements for drainage purposes are provided over:

a stormwater pipe if the nominal pipe diameter exceeds 300mm;

- b. an overland flow path where it crosses more than one property; and
- C. inter-allotment drainage infrastructure.

Note - Refer to Planning scheme policy - Integrated design for details and examples.

Note - Stormwater drainage easement dimensions are provided in accordance with Section 3.8.5 of QUDM.

Additional criteria for development for a Park⁽⁵⁷⁾

PO60

Development for a Park⁽⁵⁷⁾ ensures that the design and layout responds to the nature of the overland flow affecting the premises such that:

- public benefit and enjoyment is maximised;
- impacts on the asset life and integrity of park structures is minimised;
- maintenance and replacement costs are C. minimised.

AO60

Development for a Park⁽⁵⁷⁾ ensures works are provided in accordance with the requirements set out in Appendix B of the Planning scheme policy - Integrated Design.

Riparian and wetland setbacks (refer Overlay map - Riparian and wetland setback to determine if the following assessment criteria apply)

Note - - W1, W2 and W3 waterway and drainage lines, and wetlands are mapped on Schedule 2, Section 2.5 Overlay Maps - Riparian and wetland setbacks.

PO61

Lots are designed to:

- minimise the extent of encroachment into the riparian and wetland setback;
- ensure the protection of wildlife corridors and b. connectivity;
- reduce the impact on fauna habitats; C.
- minimise edge effects; d.
- ensure an appropriate extent of public access e. to waterways and wetlands.

AO61

Reconfiguring a lot ensures that:

- no new lots are created within a riparian and wetland setback;
- new public roads are located between the riparian and b. wetland setback and the proposed new lots.

Note - Riparian and wetlands are mapped on Schedule 2, Section 2.5 Overlay Maps – Riparian and wetland setbacks.

Scenic amenity (refer Overlay map - Scenic amenity to determine if the following assessment criteria apply)

Note - The identification of a development footprint will assist in demonstrating compliance with the following performance criteria.

PO62

Lots are sited, designed and oriented to:

- maximise the retention of existing trees and land cover including the preservation of ridgeline vegetation
- b. maximise the retention of highly natural and vegetated areas and natural landforms by minimising the use of cut and fill;
- c. ensure that buildings and structures are not located on a hill top or ridgeline;
- d. ensure that roads, driveways and accessways go across land contours, and do not cut straight up slopes and follow natural contours, not resulting in batters or retaining walls being greater than 1.5m in height.

3838 Commenced 1 February 2016 Moreton Bay Regional Council Planning Scheme