### 9.4.1.2 Community facilities zone

#### 9.4.1.2.1 Purpose - Community facilities zone

- 1. The purpose of this part of the Reconfiguring a lot code is to facilitate and manage the outcomes of development for reconfiguring a lot and its associated Operational Works in the Community facilities zone, to achieve the Overall Outcomes.
- 2. The purpose of this part of the code will be achieved through the overall outcomes as identified in Part 9.4.1 -Reconfiguring a lot code and the following additional Community facilities zone specific overall outcomes:
- a. Reconfiguring a lot maintains lots of sufficient size and dimension to facilitate development of a scale and intensity consistent with the applicable precinct.
- b. Lots created for community facilities purposes are strategically located to best service their catchment, whilst having regard to possible impacts on, and from, surrounding uses and infrastructure.
- c. Reconfiguring a lot avoids areas subject to constraint, limitation, or environmental values. Where reconfiguring a lot cannot avoid these identified areas, it responds by:
  - i. adopting a 'least risk, least impact' approach when designing, siting and locating development to minimise the potential risk to people, property and the environment;
  - ii. ensuring no further instability, erosion or degradation of the land, water or soil resource;
  - iii. maintaining environmental values, including natural, ecological, biological, aquatic, hydrological and amenity values, and enhancing these values through the provision of environmental offsets, landscaping and facilitating safe wildlife movement through the environment;
  - iv. protecting native species and protecting and enhancing native species habitat;
  - v. protecting and preserving the natural, aesthetic, architectural historic and cultural values of significant trees, places, objects and buildings of heritage and cultural significance;
  - vi. establishing effective separation distances, buffers and mitigation measures associated with major infrastructure to minimise adverse effects on sensitive land uses from noise, dust and other nuisance generating activities;
  - vii. ensuring it promotes and does not undermine the ongoing viability, integrity, operation, maintenance and safety of major infrastructure;
  - viii. Ensuring effective and efficient disaster management response and recovery capabilities.
- d. The Reconfiguring a lot, Operational works associated with the Reconfiguring a lot, and uses expected to occur as a result of the Reconfiguring a lot:
  - i. responds to the risk presented by overland flow and minimises risk to personal safety;
  - ii. is resilient to overland flow impacts by ensuring the siting and design accounts for the potential risks to property associated with overland flow;
  - iii. does not impact on the conveyance of overland flow up to and including the Overland Flow Defined Flood Event;
  - iv. directly, indirectly and cumulatively avoids an increase in the severity of overland flow and potential for damage on the premises or to a surrounding property.
- e. Reconfiguring a lot achieves the intent and purpose of the Community facilities zone outcomes as identified in Part 6 or where in the Redcliffe Kippa-Ring local plan area, achieves the intent and purpose of the Redcliffe Kippa-Ring local plan and applicable precinct as identified in Part 7.

#### 9.4.1.2.2 Requirement for assessment

#### Part C - Criteria for assessable development - Community facilities zone

Where development is categorised as assessable development - code assessment in the Table of Assessment, the assessment benchmarks are the criteria set out in Part C, Table 9.4.1.2.1 as well as the purpose statement and overall outcomes of this code.

Where development is categorised as assessable development - impact assessable, the assessment benchmarks become the whole of the planning scheme.

|  | Table 9.4.1.2.1 | Assessable ( | development | - Community | / facilities zone |
|--|-----------------|--------------|-------------|-------------|-------------------|
|--|-----------------|--------------|-------------|-------------|-------------------|

| Performance outcomes  |  | Examples that achieve aspects of the Performance Outcomes |  |  |
|---|--|---|--|--|
| Lot   | size and design  |   |  |  |
| PO1   |  | No example provided.                                      |  |  |
| Lots are of sufficient size and design to accommodate<br>land uses consistent in the zone and applicable<br>precinct with regard to areas required for: |  |   |  |  |
| a.  | buildings and associated structures;   |   |  |  |
| b.  | convenient and safe access;  |   |  |  |
| c.  | on-site car parking;   |   |  |  |
| d.  | on-site manoeuvring to ensure vehicle egress and access in forward gear;                             |   |  |  |
| e.  | appropriately sited loading and servicing areas;   |   |  |  |
| f.  | setbacks, buffers and landscaping where required;  |   |  |  |
| g.  | maintaining the required level of functionality during and immediately after a natural hazard event. |   |  |  |
| Note - refer to the overall outcomes for the Community facilities zone for a list of consistent uses.   |  |   |  |  |
| Boundary realignment  |  |   |  |  |
| PO2   | 2  | No example provided.                                      |  |  |
| Boundary alignments ensure that infrastructure and services are wholly contained within the lot they serve.   |  |   |  |  |
| PO3   | }  | No example provided.                                      |  |  |
| Bou   | ndary realignment does not result in:  |   |  |  |
| a.  | existing land uses on-site becoming non-complying with planning scheme criteria;                     |   |  |  |
| b.  | lots being unserviced by infrastructure;   |   |  |  |
| c.  | lots not providing for own private servicing.  |   |  |  |
| Not<br>a.   | e - Examples of a. above may include but are not limited to:<br>minimum lot size requirements;       |   |  |  |

### 9 Development codes

| b.  | setbacks   |                      |
|---|--|----------------------|
| c. parking and access requirements;   |  |                      |
| d. servicing and Infrastructure requirements;   |  |                      |
| e.  | dependant elements of an existing or approved land use being separately titled, including but not limited to:  |                      |
|   | <ul> <li>Where premises is approved as Multiple<br/>dwelling<sup>(49)</sup> with a communal open space area,<br/>the communal open space cannot be separately<br/>titled as it is required by the Multiple dwelling<br/>approval.</li> </ul>   |                      |
|   | ii. Where a commercial or industrial land use contains<br>an ancillary office <sup>(53)</sup> , the office <sup>(53)</sup> cannot be<br>separately titled as it is considered part of the<br>commercial or industrial use.   |                      |
|   | iii. Where a Dwelling house <sup>(22)</sup> includes a secondary dwelling or associated outbuildings, they cannot be separately titled as they are dependent on the Dwelling house <sup>(22)</sup> use.  |                      |
|   |  |                      |
| PO4   |  | No example provided. |
| Boundary realignment results in lots which have appropriate size, dimensions and access to cater for uses consistent with the precinct.   |  |                      |
| Note - Refer to overall outcomes for the Community Facilities zone - and relevant precinct for uses consistent in this precinct.  |  |                      |
| Reco  | onfiguring existing development by Communi   | ty Title             |
| PO5   |  | No example provided. |
| Reco<br>comr<br><i>Corp</i><br>unde<br>uses<br>opera  | Infiguring a lot which creates or amends a<br>nunity title scheme as described in the <i>Body</i><br><i>orate and Community Management Act 1997</i> is<br>rtaken in a way that does not result in existing<br>on the land becoming unlawful or otherwise<br>ating in a manner that is: |                      |
| a.  | inconsistent with any approvals on which those   |                      |
| b.  | inconsistent with the requirements for accepted<br>development applying to those uses at the time<br>that they were established.   |                      |
| Note - Examples of land uses becoming unlawful include, but<br>are not limited to the following:  |  |                      |
| <ul> <li>a. Land on which a Dual occupancy<sup>(21)</sup> has been established is reconfigured in a way that results in both dwellings no longer being on the one lot. The reconfiguring has the effect of transforming the development from a Dual occupancy<sup>(21)</sup> to two separate Dwelling houses<sup>(22)</sup>, at least one of which does not satisfy the requirements</li> </ul> |  |                      |

| <ul> <li>for accepted development applying to Dwelling houses<sup>(22)</sup>.</li> <li>b. Land on which a Multiple dwelling<sup>(49)</sup> has been established is reconfigured in a way that precludes lawful access to required communal facilities by either incorporating some of those facilities into private lots or otherwise obstructing the normal access routes to those facilities. Those communal facilities may have been required under the requirements for accepted development for the use or conditions of development approval.</li> <li>Editor's note -To satisfy this performance outcome, the development application may need to be a combined application for reconfiguring a lot and a material change of use or otherwise be supported by details that confirm that the land use still satisfies all relevant land use requirements.</li> </ul>  |                      |
|---|----------------------|
| Reconfiguring by Lease  |                      |
| PO6   | No example provided. |
| <ul> <li>Reconfiguring a lot which divides land or buildings by lease in a way that allows separate occupation or use of those facilities is undertaken in a way that does not result in existing uses on the land becoming unlawful or otherwise operating in a manner that is:</li> <li>a. inconsistent with any approvals on which those uses rely; or</li> <li>b. inconsistent with the requirements for accepted development applying to those uses at the time that they were established.</li> <li>Note - An example of a land use becoming unlawful is a Multiple dwelling<sup>(49)</sup> over which one or more leases have been created in a way that precludes lawful access to some of the required communal facilities. Some of the communal car parking facilities have been incorporated into lease areas while other leases are located in a way that obstructs the normal access routes to other communal facilities. Those communal facilities may have been required under the requirements for accepted development for the use or conditions of development approval, but they are no longer freely available to all occupants of the Multiple dwelling<sup>(49)</sup>.</li> </ul> |                      |
| Editor's note - To satisfy this performance outcome, the development application may need to be supported by details that confirm that the land use still satisfies all relevant land use requirements.   |                      |
| Editor's note – Under the definition in Schedule 2 of the Act, the following do not constitute reconfiguring a lot and are not subject to this performance outcome:   |                      |
| <ul> <li>a. a lease for a term, including renewal options, not exceeding 10 years; and</li> <li>b. an agreement for the exclusive use of part of the common property for a community titles scheme under the <i>Body Corporate and Community Management Act 1997</i>.</li> </ul>  |                      |
| Volumetric subdivision  |                      |

| P07  |   | No example provided.  |   |  |
|--|---|---|---|--|
| The reconfiguring of the space above or below the<br>surface of the land ensures appropriate area,<br>dimensions and access arrangements to cater for<br>uses consistent with the precinct and does not result<br>in existing land uses on-site becoming non-complying<br>with planning scheme criteria. |   |   |   |  |
| Not  | e - An example may include but are not limited to:  |   |   |  |
| a.   | where a Dwelling house <sup>(22)</sup> includes a secondary dwelling<br>or associated outbuildings, they cannot be separately<br>titled as they are dependent on the Dwelling house <sup>(22)</sup><br>use.   |   |   |  |
| Reti   | culated supply  |   |   |  |
| PO8  |   | E8  |   |  |
| Eacl<br>serv<br>storn<br>and<br>a.<br>b.<br>c.<br>d.<br>d.<br>e.<br>f.<br>g.   | h lot is provided with an appropriate level of<br>ice and infrastructure, including water supply,<br>mwater management, sewage disposal,<br>mwater drainage, electricity, telecommunications<br>gas (if available) in a manner that:<br>is efficient in delivery of service;<br>is effective in delivery of service;<br>is conveniently accessible in the event of<br>maintenance or repair;<br>minimises whole of life cycle costs for that<br>infrastructure;<br>minimises risk of potential adverse impacts on<br>the natural and built environment;<br>minimises risk of potential adverse impact on<br>amenity and character values;<br>recognises and promotes Councils Total Water<br>Cycle Management policy and the efficient use<br>of water resources. | Lots are<br>a. a cu<br>infr<br>b. a cu<br>c. a cu<br>net<br>d. a p<br>net<br>higi | provided with:<br>onnection to the reticulated water supply<br>astructure network;<br>onnection to the sewerage infrastructure network;<br>onnection to the reticulated electricity infrastructure<br>work; and<br>hysical connection to the telecommunication<br>work, that where available to the land is part of the<br>h speed broadband network. |  |
| Stor   | mwater location and design  |   |   |  |
| PO   |   | E9  |   |  |
| Lots are of a sufficient grade to accommodate effective stormwater drainage to a lawful point of discharge.  |   | The surfa<br>and slope<br>of discha   | ace level of a lot is at a minimum grade of 1:100<br>es towards the street frontage, or other lawful point<br>Irge  |  |

No example provided.

PO10

| The development is planned and designed considering<br>the land use constraints of the site and incorporates<br>water sensitive urban design principles.                                    |   |
|---|---|
| PO11  | No example provided.  |
| Stormwater drainage pipes and structures through or<br>within private land are protected by easements in<br>favour of Council with sufficient area for practical<br>access for maintenance. |   |
|   |   |
| PO12  | No example provided.  |
| Stormwater management facilities are located outside<br>of riparian areas and prevent increased channel bed<br>and bank erosion.  |   |
| PO13  | No example provided.  |
| Natural streams and riparian vegetation are retained and enhanced through revegetation.   |   |
| PO14  | No example provided.  |
| Areas constructed as detention basins are adaptable for passive recreation.   |   |
| PO15  | No example provided.  |
| Development maintains the environmental values of waterway ecosystems.  |   |
| PO16  | No example provided.  |
| Constructed water bodies are not dedicated as public assets.  |   |
| Stormwater management system  |   |
| PO17  | E17   |
| The major drainage system has the capacity to safely convey stormwater flows for the defined flood event.   | The roads, drainage pathways, drainage features and<br>waterways safely convey the stormwater flows for the<br>defined flood event without allowing flows to encroach upon<br>private lots. |
| PO18  | E18   |
| Overland flow paths (for any storm event) from roads<br>and public open space areas do not pass through<br>private lots.  | Drainage pathways are provided to accommodate overland flows from roads and public open space areas.  |

| PO1   | 9  | No example provided. |
|---|--|----------------------|
| Where located within the Upper Pine, Hays Inlet and<br>Burpengary Creek catchments, development achieves<br>the greater pollutant removal of:   |  |                      |
| a.  | 100% reductions in mean annual loads from<br>unmitigated development for total suspended<br>solids, total phosphorus, total nitrogen and gross<br>pollutants >5mm; |                      |
| b.  | the design objectives in Table A and B in Appendix 2 of the SPP.   |                      |
| Note - To demonstrate compliance with this PO a stormwater<br>quality management plan is to be prepared by a suitable qualified<br>person demonstrating compliance with the Urban Stormwater<br>Planning Guideline 2010 and considering any local area<br>stormwater management planning prepared by Council. |  |                      |
| Note<br>catc  | e - Refer to Overlay map - Stormwater catchments for<br>hment boundaries.  |                      |
| PO2   | 0  | No example provided. |
| Where located outside the Upper Pine, Hays Inlet and<br>Burpengary Creek catchments, development achieves<br>the design objectives in Tables A and B in Appendix<br>2 of the SPP.   |  |                      |
| Note - To demonstrate compliance with this PO a stormwater<br>quality management plan is to be prepared by a suitable qualified<br>person demonstrating compliance with the Urban Stormwater<br>Planning Guideline 2010 and considering any local area<br>stormwater management planning prepared by Council. |  |                      |
| Note<br>catc  | e - Refer to Overlay map - Stormwater catchments for hment boundaries.   |                      |
| PO2   | 1  | No example provided. |
| The   | stormwater management system is designed to:   |                      |
| a.  | protect the environmental values in downstream waterways;  |                      |
| b.  | maintain ground water recharge areas;  |                      |
| C.  | preserve existing natural wetlands and associated vegetation buffers;  |                      |
| d.  | avoid disturbing soils or sediments;   |                      |
| e.  | avoid altering the natural hydrologic regime in acid sulphate soil and nutrient hazardous areas;   |                      |
| f.  | maintain and improve receiving water quality;  |                      |
| g.  | protect natural waterway configuration;  |                      |

| h.                   | protect downstream and adjacent properties;  |  |
|----------------------|--|--|
| i.                   | protect and enhance riparian areas.  |  |
| PO2                  | 2  | No example provided.   |
| Desi<br>man          | gn and construction of the stormwater agement system:  |  |
| a.                   | utilise methods and materials to minimise the<br>whole of lifecycle costs of the stormwater<br>management system; and  |  |
| b.                   | are coordinated with civil and other landscaping works.  |  |
| Note<br>syst<br>desi | e - To determine the standards for stormwater management<br>em construction refer to Planning scheme policy - Integrated<br>gn.  |  |
| Nati                 | ve vegetation where not located in the Enviror   | nmental areas overlay  |
| PO2                  | 3  | No example provided.   |
| Reco<br>vege         | onfiguring a lot facilitates the retention of native etation by:   |  |
| a.                   | incorporating native vegetation and habitat trees<br>into the overall subdivision design, development<br>layout, on-street amenity and landscaping where<br>practicable;   |  |
| b.                   | ensuring habitat trees are located outside a<br>development footprint. Where habitat trees are<br>to be cleared, replacement fauna nesting boxes<br>are provided at the rate of 1 nest box for every<br>hollow removed. Where hollows have not yet<br>formed in trees > 80cm in diameter at 1.3m<br>height, 3 nest boxes are required for every<br>habitat tree removed. |  |
| C.                   | providing safe, unimpeded, convenient and ongoing wildlife movement;   |  |
| d.                   | avoiding creating fragmented and isolated patches of native vegetation.  |  |
| e.                   | ensuring that biodiversity quality and integrity of<br>habitats is not adversely impacted upon but are<br>maintained and protected;  |  |
| f.                   | ensuring that soil erosion and land degradation does not occur;  |  |
| g.                   | ensuring that quality of surface water is not<br>adversely impacted upon by providing effective<br>vegetated buffers to water bodies.  |  |
| Nois                 | Se   |  |
| PO2                  | 4  | E24  |
| Nois<br>fenc         | e attenuation structure (e.g. walls, barriers or es):  | Noise attenuation structures (e.g. walls, barriers or fences): |

### 9 Development codes

| <ul> <li>a. contribute to safe and usable public spaces,<br/>through maintaining high levels of surveillance<br/>of parks, streets and roads that serve active<br/>transport purposes (e.g. existing or future<br/>pedestrian paths or cycle lanes etc);</li> <li>b. maintain the amenity of the streetscape.</li> <li>Note - A noise impact assessment may be required to<br/>demonstrate compliance with this PO. Noise impact</li> </ul> |  | a.<br>i.<br>ii.<br>b.       | are not visible from an adjoining road or public area<br>unless;<br>adjoining a motorway or rail line; or<br>adjoining part of an arterial road that does not serve<br>an existing or future active transport purpose (e.g.<br>pedestrian paths or cycle lanes) or where attenuation<br>through building location and materials is not possible.<br>do not remove existing or prevent future active |
|---|--|-----------------------------|---|
| scheme policy - Noise.<br>Note - Refer to Planning Scheme Policy – Integrated design for<br>details and examples of noise attenuation structures.   |  | Note<br>and<br>Note<br>tran | with Planning scheme policy - Integrated design.<br>e - Refer to Planning Scheme Policy – Integrated design for details<br>examples of noise attenuation structures.<br>e - Refe80r to Overlay map – Active transport for future active<br>sport routes.  |
|   |  |                             |   |

#### Values and constraints criteria

Note - The relevant values and constraints criteria do not apply where the development is consistent with a current Development permit for Reconfiguring a lot or Material change of use or Operational work, where that approval has considered and addressed (e.g. through a development footprint plan (or similar in the case of Landslide hazard) or conditions of approval) the identified value or constraint under this planning scheme.

## Bushfire hazard (refer Overlay map - Bushfire hazard to determine if the following assessment criteria apply)

Note - The preparation of a bushfire management plan in accordance with Planning scheme policy – Bushfire prone areas can assist in demonstrating compliance with the following performance criteria. The identification of a development footprint will assist in demonstrating compliance with the following performance criteria.

| PO25                  |  | E25   |   |  |  |
|-----------------------|--|---|---|--|--|
| Lots are designed to: |  | Reconfiguring a lot ensures that all new lots are of an appropriate size, shape and layout to allow for the siting of |   |  |  |
| a.                    | minimise the risk from bushfire hazard to each<br>lot and provide the safest possible siting for   | futu  | future buildings being located:   |  |  |
|                       | buildings and structures;  | a.  | within an appropriate development footprint;  |  |  |
| b.                    | limit the possible spread paths of bushfire within the reconfiguring:  | b.  | within the lowest hazard locations on a lot;  |  |  |
| C                     | c.<br>achieve sufficient separation distance between<br>development and hazardous vegetation to<br>minimise the risk to future buildings and<br>structures during bushfire events; | c.  | to achieve minimum separation between development<br>or development footprint and any source of bushfire  |  |  |
| c. a<br>d<br>n<br>s   |  |   | hazard of 20m or the distance required to achieve a<br>Bushfire Attack Level BAL (as identified under<br>AS3959-2009), whichever is the greater;  |  |  |
| d.                    | maintain the required level of functionality for<br>emergency services and uses during and<br>immediately after a natural hazard event.  | d.  | to achieve a minimum separation between<br>development or development footprint and any retained<br>vegetation strips or small areas of vegetation of 10m<br>or the distance required to achieve a Bushfire Attack<br>Level BAL (as identified under AS3959-2009),<br>whichever is the greater; |  |  |
|                       |  | e.  | away from ridgelines and hilltops;  |  |  |

|  | f. on land with a slope of less than 15%;   |
|--|---|
|  | g. away from north to west facing slopes.   |
| PO26   | E26   |
| Lots provide adequate water supply and inf   | rastructure For water supply purposes, reconfiguring a lot ensures that:  |
| to oupport into righting.  | a. Lots have access to a reticulated water supply provided by a distributer retailer for the area; or   |
|  | <ul> <li>where no reticulated water supply is available, on-site fire fighting water storage containing not less than 10 000 litres and located within a development footprint.</li> </ul>  |
| PO27   | E27   |
| Lots are designed to achieve:  | Reconfiguring a lot ensures a new lot is provided with:   |
| a. safe site access by avoiding potentia   | a. direct road access and egress to public roads;   |
| <ul> <li>b. accessibility and manoeuvring for fire<br/>during bushfire.</li> </ul>   | b. an alternative access where the private driveway is<br>longer than 100m to reach a public road;  |
|  | c. driveway access to a public road that has a gradient no greater than 12.5%;  |
|  | d. minimum width of 3.5m.   |
|  |   |
| PO28   | E28   |
| <b>PO28</b><br>The road layout and design supports:  | E28<br>Reconfiguring a lot provides a road layout which:  |
| <ul> <li>PO28</li> <li>The road layout and design supports:</li> <li>a. safe and efficient emergency service to all lots; and manoeuvring within the subdivision;</li> </ul>   | E28         Reconfiguring a lot provides a road layout which:         as access e         a. includes a perimeter road that separating the new lots from hazardous vegetation on adjacent lots incorporating by:  |
| <ul> <li>PO28</li> <li>The road layout and design supports:</li> <li>a. safe and efficient emergency service to all lots; and manoeuvring within the subdivision;</li> <li>b. availability and maintenance of acceptor for the purpose of safe evacuation.</li> </ul>              | E28         Reconfiguring a lot provides a road layout which:         a. includes a perimeter road that separating the new lots from hazardous vegetation on adjacent lots incorporating by:         ss routes       i. a cleared width of 20m;   |
| <ul> <li>PO28</li> <li>The road layout and design supports:</li> <li>a. safe and efficient emergency service to all lots; and manoeuvring within the subdivision;</li> <li>b. availability and maintenance of accertor for the purpose of safe evacuation.</li> </ul>              | E28         Reconfiguring a lot provides a road layout which:         a.       includes a perimeter road that separating the new lots from hazardous vegetation on adjacent lots incorporating by:         ss routes       i.       a cleared width of 20m;         ii.       road gradients not exceeding 12.5%;   |
| <ul> <li>PO28</li> <li>The road layout and design supports: <ul> <li>a. safe and efficient emergency service to all lots; and manoeuvring within the subdivision;</li> </ul> </li> <li>b. availability and maintenance of access for the purpose of safe evacuation.</li> </ul>    | E28         Reconfiguring a lot provides a road layout which:         a.       includes a perimeter road that separating the new lots from hazardous vegetation on adjacent lots incorporating by:         ss routes       i.       a cleared width of 20m;         ii.       road gradients not exceeding 12.5%;         iii.       pavement and surface treatment capable of being used by emergency vehicles;  |
| <ul> <li>PO28</li> <li>The road layout and design supports: <ul> <li>a. safe and efficient emergency service to all lots; and manoeuvring within the subdivision;</li> </ul> </li> <li>b. availability and maintenance of access for the purpose of safe evacuation.</li> </ul>    | E28Reconfiguring a lot provides a road layout which:a. includes a perimeter road that separating the new lots<br>from hazardous vegetation on adjacent lots<br>incorporating by:ss routesi. a cleared width of 20m;ii. road gradients not exceeding 12.5%;iii. pavement and surface treatment capable of<br>being used by emergency vehicles;iv. Turning areas for fire fighting appliances in<br>accordance with Qld Fire and Emergency<br>Services' Fire Hydrant and Vehicle Access<br>Guidelines.  |
| <ul> <li>PO28</li> <li>The road layout and design supports: <ul> <li>a. safe and efficient emergency service to all lots; and manoeuvring within the subdivision;</li> </ul> </li> <li>b. availability and maintenance of accerding for the purpose of safe evacuation.</li> </ul> | E28Reconfiguring a lot provides a road layout which:a. includes a perimeter road that separating the new lots<br>from hazardous vegetation on adjacent lots<br>incorporating by:ss routesi. a cleared width of 20m;ii. road gradients not exceeding 12.5%;iii. pavement and surface treatment capable of<br>being used by emergency vehicles;iv. Turning areas for fire fighting appliances in<br>accordance with Qld Fire and Emergency<br>Services' Fire Hydrant and Vehicle Access<br>Guidelines.b. Or if the above is not practicable, a fire maintenance<br>trail separates the lots from hazardous vegetation on<br>adjacent lots incorporating:  |
| <ul> <li>PO28</li> <li>The road layout and design supports: <ul> <li>a. safe and efficient emergency service to all lots; and manoeuvring within the subdivision;</li> </ul> </li> <li>b. availability and maintenance of accerding for the purpose of safe evacuation.</li> </ul> | E28         Reconfiguring a lot provides a road layout which:         as access         a. includes a perimeter road that separating the new lots from hazardous vegetation on adjacent lots incorporating by:         as routes         i. a cleared width of 20m;         ii. road gradients not exceeding 12.5%;         iii. pavement and surface treatment capable of being used by emergency vehicles;         iv. Turning areas for fire fighting appliances in accordance with Qld Fire and Emergency Services' Fire Hydrant and Vehicle Access Guidelines.         b. Or if the above is not practicable, a fire maintenance trail separates the lots from hazardous vegetation on adjacent lots incorporating:         i. a minimum cleared width of 6m and minimum formed width of 4m; |

|    | iii.                  | cross slope not exceeding 10%;  |
|----|-----------------------|---|
|    | iv.                   | a formed width and erosion control devices to<br>the standards specified in Planning scheme<br>policy - Integrated design;                  |
|    | V.                    | a turning circle or turnaround area at the end of<br>the trail to allow fire fighting vehicles to<br>manoeuvre;                             |
|    | vi.                   | passing bays and turning/reversing bays every 200m;   |
|    | vii.                  | an access easement that is granted in favour of<br>the Council and the Queensland Fire and Rescue<br>Service or located on public land.     |
| C. | exclu<br>with<br>haza | udes cul-de-sacs, except where a perimeter road<br>a cleared width of 20m isolates the lots from<br>ardous vegetation on adjacent lots; and |
| d. | excl                  | udes dead-end roads.  |

# Environmental areas (refer Overlay map - Environmental areas to determine if the following assessment criteria apply)

Note - The identification of a development footprint will assist in demonstrating compliance with the following performance criteria.

Editors' Note - The accuracy of overlay mapping can be challenged through the development application process (code assessable development) or by way of a planning scheme amendment. See Council's website for details.

| PO29   |  | No example provided.   |
|--|--|--|
| No new boundaries are to occur within 4m of a High Value Area. |  |  |
| PO30   |  | E30  |
| Lots   | are designed to:   | Reconfiguring a lot ensures that no additional lots are created within a Value Offset Area |
| a.   | minimise the extent of encroachment into the MLES waterway buffer or a MLES wetland buffer;  |  |
| b.   | ensure quality and integrity of biodiversity and<br>ecological values is not adversely impacted upon<br>but are maintained and protected;                              |  |
| C.   | incorporate native vegetation and habitat trees<br>into the overall subdivision design, development<br>layout, on-street amenity and landscaping where<br>practicable; |  |
| d.   | provide safe, unimpeded, convenient and<br>ongoing wildlife movement;  |  |
| e.   | avoid creating fragmented and isolated patches of native vegetation;   |  |

| the   |  |  |
|---|--|--|
|   |  |  |
|   |  |  |
|   |  |  |
|   |  |  |
|   |  |  |
| wing  |  |  |
|   |  |  |
|   |  |  |
|   |  |  |
| Heritage and landscape character (refer Overlay map - Heritage and landscape character to determine if the following assessment criteria apply) |  |  |
| Note - The identification of a development footprint will assist in demonstrating compliance with the following performance criteria.           |  |  |
|   |  |  |
|   |  |  |
|   |  |  |
|   |  |  |

| <ul> <li>create the potential to adversely affect views to<br/>and from the heritage place, building, item or<br/>object;</li> </ul>  |  |
|---|--|
| c. obscure or destroy any pattern of historic subdivision, historical context, landscape setting or the scale and consistency of the urban fabric relating to the local heritage place.   |  |
| PO35  | No example provided.   |
| Reconfiguring a lot retains significant trees and incorporates them into the subdivision design, development layout and provision of infrastructure.  |  |
| Infrastructure buffers (refer to Overlay map - Infrast<br>criteria apply)   | tructure buffers to determine if the following assessment  |
| Note - The identification of a development footprint will assist in de  | emonstrating compliance with the following performance standards.  |
| Bulk water supply infrastructure  |  |
| PO36  | No example provided.   |
| Reconfiguration of lots does not compromise or<br>adversely impact upon the efficiency and integrity of<br>Bulk water supply infrastructure.  |  |
| PO37  | E37  |
| Reconfiguring of lots ensures that access requirements of Bulk water supply infrastructure are maintained.  | Bulk water supply infrastructure traversing or within private<br>land are protected by easement in favour of the service<br>provider for access and maintenance. |
| PO38  | E38  |
| Development within a Bulk water supply infrastructure buffer:   | New lots provide a development footprint outside the Bulk water supply infrastructure buffer.  |
| <ul> <li>a. is located, designed and constructed to protect<br/>the integrity of the water supply pipeline;</li> <li>b. maintains adequate access for any required<br/>maintenance or upgrading work to the water<br/>supply pipeline.</li> </ul> |  |
| PO39  | No example provided.   |
| Boundary realignments:  |  |
| i. do not result in the creation of additional building development opportunities within the buffer;  |  |
| ii. results in the reduction of building development opportunities within the buffer.   |  |
| Gas pipeline buffer   |  |

| PO40  | No example provided.   |
|---|--|
| New lots provide a development footprint outside of the buffer.   |  |
| PO41  | No example provided.   |
| The creation of new lots does not compromise or adversely impact upon the efficiency and integrity of supply.   |  |
| PO42  | No example provided.   |
| The creation of new lots does not compromise or<br>adversely impact upon access to the supply line for<br>any required maintenance or upgrading work. |  |
| PO43  | No example provided.   |
| Boundary realignments:  |  |
| i. do not result in the creation of additional building development opportunities within the buffer;  |  |
| ii. results in the reduction of building development opportunities within the buffer.   |  |
| High voltage electricity line buffer  |  |
| PO44  | No example provided.   |
| Lots provide a development footprint outside of the buffer.   |  |
| PO45  | E45  |
| Adequate buffers are provided between utilities and dwellings to protect residential amenity and health.  | New lots provide a development footprint for utilities and dwellings outside of the buffer |
| PO46  | E46  |
| The creation of new lots does not compromise or adversely impact upon the efficiency and integrity of supply.   | No new lots are created within the buffer area.  |
| PO47  | E47  |
| The creation of new lots does not compromise or<br>adversely impact upon access to the supply line for<br>any required maintenance or upgrading work. | No new lots are created within the buffer area.  |
| PO48  | No example provided.   |
| Boundary realignments:  |  |

| i.   | do not result in the creation of additional building development within the buffer;               |   |  |
|--|---|---|--|
| ii.  | result in the reduction of building development opportunities within the buffer.                  |   |  |
| Land   | fill buffer   |   |  |
| PO49   |   | No example provided.  |  |
| New lots provide a development footprint outside of the buffer.  |   |   |  |
| PO50   |   | No example provided.  |  |
| Boun   | dary realignments:  |   |  |
| i.   | do not result in the creation of additional building development opportunities within the buffer; |   |  |
| ii.  | results in the reduction of building development opportunities within the buffer.                 |   |  |
| Wastewater treatment site buffer   |   |   |  |
| PO51   |   | No example provided.  |  |
| New lots provide a development footprint outside of the buffer.  |   |   |  |
| PO52   |   | No example provided.  |  |
| Boun   | dary realignments:  |   |  |
| i.   | do not result in the creation of additional building development opportunities within the buffer; |   |  |
| ii.  | results in the reduction of building development opportunities within the buffer.                 |   |  |
| Landslide hazard (refer Overlay map - Landslide hazard to determine if the following assessment criteria apply)  |   |   |  |
| Note -The preparation of a site-specific geotechnical assessment report in accordance with Planning scheme policy – Landslide hazard can assist in demonstrating compliance with the following performance criteria. The identification of a development footprint on will assist in demonstrating compliance with the following performance criteria. |   |   |  |
| PO53   |   | E53.1   |  |
| Lots e   | ensure that:<br>future building location is located in part of a site                             | Lots provides a development footprint for all lots free from risk of landslide. |  |
| not subject to landslide risk;   |   | E53.2   |  |

| b.  | the r<br>finis<br>clea<br>avoi | need for excessive on-site works, change to<br>hed landform, or excessive vegetation<br>rance to provide for future development is<br>ded; | Development footprints and driveways for lots does not exceed 15% slope. |
|-----|--------------------------------|--|--|
| C.  | ther<br>patte                  | e is minimal disturbance to natural drainage<br>erns;  |  |
| d.  | eart                           | hworks do not:   |  |
|     | i.                             | involve cut and filling having a height greater than 1.5m;   |  |
|     | ii.                            | involve any retaining wall having a height greater than 1.5m;  |  |
|     | iii.                           | involve earthworks exceeding 50m <sup>3</sup> ,  |  |
|     | iv.                            | redirect or alter the existing flows of surface or groundwater:  |  |
| e.  | deve<br>mair<br>and            | elopment can be located and designed to<br>ntain the required level of functionality during<br>immediately after a natural hazard event.   |  |
| Ovo | rland                          | flow path (rofor Ovorlay map - Ovorland fl   | ow path to dotorming if the following assessment criteria                |

# Overland flow path (refer Overlay map - Overland flow path to determine if the following assessment criteria apply)

Note - The applicable river and creek flood planning levels associated with defined flood event (DFE) within the inundation area can be obtained by requesting a flood check property report from Council.

| PO54                 |   | No example provided.  |
|----------------------|---|---|
| Development:         |   |   |
| a.<br>b.             | minimises the risk to persons from overland flow;<br>does not increase the potential for damage from<br>overland flow either on the premises or on a<br>surrounding property, public land, road or<br>infrastructure. |   |
| PO55                 |   | E55   |
| Development:         |   | Development ensures that any buildings are not located in an Overland flow path area.   |
| a.                   | for the fully developed upstream catchment;   | Note: A report from a suitably qualified Registered Professional Engineer<br>Queensland is required certifying that the development does not increase<br>the potential for significant adverse impacts on an upstream, downstream<br>or surrounding property. |
| b.                   | does not concentrate, intensify or divert overland<br>flow onto an upstream, downstream or<br>surrounding property.   |   |
| Note<br>sche<br>flow | e - Reporting to be prepared in accordance with Planning<br>eme policy – Flood hazard, Coastal hazard and Overland<br>/   |   |

| POSS   |   | No example provided   |
|--|---|---|
|  |   |   |
| Dev  | elopment does not:  |   |
| a.<br>b.<br>Note<br>an a<br>may  | directly, indirectly or cumulatively cause any<br>increase in overland flow velocity or level;<br>increase the potential for flood damage from<br>overland flow either on the premises or on a<br>surrounding property, public land, road or<br>infrastructure. |   |
| Note<br>Eng<br>doe<br>on a   | e - A report from a suitably qualified Registered Professional<br>ineer Queensland is required certifying that the development<br>s not increase the potential for significant adverse impacts<br>in upstream, downstream or surrounding premises.              |   |
| Note<br>sche<br>flow   | e - Reporting to be prepared in accordance with Planning<br>eme policy – Flood hazard, Coastal hazard and Overland  |   |
| PO5  | 7   | E57   |
| Development ensures that overland flow is not<br>conveyed from a road or public open space onto a<br>private lot, unless the development is in a Rural zone.   |   | Development ensures that overland flow paths and drainage<br>infrastructure is provided to convey overland flow from a<br>road or public open space area away from a private lot,<br>unless the development is in the Rural zone.   |
| PO5  | 8   | E58.1   |
| Development ensures that Council and inter-allotment<br>drainage infrastructure, overland flow paths and open<br>drains through private property cater for overland flows<br>for a fully developed upstream catchment flows and<br>are able to be easily maintained.<br>Note - A report from a suitably qualified Registered Professional<br>Engineer Queensland is required certifying that the development<br>does not increase the potential for significant adverse impacts<br>on an upstream, downstream or surrounding premises. |   | Development ensures that roof and allotment drainage<br>infrastructure is provided in accordance with the following<br>relevant level as identified in QUDM:<br>a. Urban area – Level III;<br>b. Rural area – N/A;<br>c. Industrial area – Level V;<br>d. Commercial area – Level V.<br>E58.2 |
| Note<br>sche<br>flow   | e - Reporting to be prepared in accordance with Planning<br>eme policy – Flood hazard, Coastal hazard and Overland  | Development ensures that all Council and allotment drainage<br>infrastructure is designed to accommodate any event up to<br>and including the 1% AEP for the fully developed upstream<br>catchment.   |
| PO59   |   | No example provided   |
| Development protects the conveyance of overland<br>flow such that easements for drainage purposes are<br>provided over:  |   |   |
| a.   | a stormwater pipe if the nominal pipe diameter exceeds 300mm;   |   |

| <ul> <li>an overland flow path where it crosses more<br/>than one property; and</li> </ul>  |  |  |  |
|---|--|--|--|
| c. inter-allotment drainage infrastructure.   |  |  |  |
| Note - Refer to Planning scheme policy - Integrated design for details and examples.  |  |  |  |
| Note - Stormwater drainage easement dimensions are provided in accordance with Section 3.8.5 of QUDM.   |  |  |  |
| Additional criteria for development for a Park <sup>(57)</sup>  |  |  |  |
| PO60  | E60  |  |  |
| Development for a Park <sup>(57)</sup> ensures that the design<br>and layout responds to the nature of the overland flow<br>affecting the premises such that: | Development for a Park <sup>(57)</sup> ensures works are provided in accordance with the requirements set out in Appendix B of the Planning scheme policy - Integrated Design. |  |  |
| a. public benefit and enjoyment is maximised;   |  |  |  |
| <ul> <li>b. impacts on the asset life and integrity of park<br/>structures is minimised;</li> </ul>   |  |  |  |
| c. maintenance and replacement costs are minimised.   |  |  |  |
| Note W1, W2 and W3 waterway and drainage lines, and wetlands are mapped on Schedule 2, Section 2.5 Overlay Maps – Riparian and wetland setbacks.              |  |  |  |
| PO61  | E61  |  |  |
| Lots are designed to:   | Reconfiguring a lot ensures that:  |  |  |
| a. minimise the extent of encroachment into the riparian and wetland setback;   | a. no new lots are created within a riparian and wetland setback;  |  |  |
| <ul> <li>ensure the protection of wildlife corridors and<br/>connectivity;</li> </ul>   | b. new public roads are located between the riparian and wetland setback and the proposed new lots.  |  |  |
| c. reduce the impact on fauna habitats;   | Note Diparian and wattands are manned an Schodule 2. Section 2.5   |  |  |
| d. minimise edge effects;   | Overlay Maps – Riparian and wetland setbacks.  |  |  |
| e. ensure an appropriate extent of public access to waterways and wetlands.   |  |  |  |
| Scenic amenity (refer Overlay map - Scenic amenit   | y to determine if the following assessment criteria apply)   |  |  |
| Note - The identification of a development footprint will assist in demonstrating compliance with the following performance criteria.                         |  |  |  |
| PO62  | No example provided  |  |  |

### 9 Development codes

Lots are sited, designed and oriented to: maximise the retention of existing trees and land a. cover including the preservation of ridgeline vegetation b. maximise the retention of highly natural and vegetated areas and natural landforms by minimising the use of cut and fill; ensure that buildings and structures are not C. located on a hill top or ridgeline; d. ensure that roads, driveways and accessways go across land contours, and do not cut straight up slopes and follow natural contours, not resulting in batters or retaining walls being greater than 1.5m in height.